



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

110 SUS (24 cSt)	30 cc/min.@70 bar
	2,5 mm
	33 N/100 bar @ Port 1

: • Sun

**CONFIGURATION OPTIONS**

**Model Code Example: FMDAXCDN**

(X)	(C)	(N)	
<b>X</b>	<b>C</b> .1 - 6 gpm (0,4 - 23 L/min.)	<b>N</b>	
<b>D</b> /	<b>A</b> .1 - 1.6 gpm (0,4 - 6.1 L/min.)	<b>E</b> EPDM	<b>212</b> DIN 43650 A 12 VDC
<b>E</b> ( )	<b>B</b> .1 - 4 gpm (0,4 - 15 L/min.)	<b>V</b>	<b>224</b> DIN 43650 A 24 VDC
<b>L</b>	<b>D</b> .1 - 9 gpm (0,4 - 34 L/min.)		<b>224NX01</b> DIN 43650 A 24 VDC (TVS) XMD-01
<b>M</b>			<b>224NX02</b> DIN 43650 A 24 VDC (TVS) XMD-02
<b>T</b> ( )			<b>912</b> Deutsch DT04-2P 12 VDC
			<b>912NX01</b> Deutsch DT04-2P 12 VDC (TVS) XMD-01
			<b>912NX02</b> Deutsch DT04-2P 12 VDC (TVS) XMD-02
			<b>924</b> Deutsch DT04-2P 24 VDC
			<b>924NX01</b> Deutsch DT04-2P 24 VDC (TVS) XMD-01
			<b>924NX02</b> Deutsch DT04-2P 24 VDC (TVS) XMD-02