



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-11A
Hysteresis (with dither)	<4%
Hysteresis with DC input	<8%
Linearity (with dither)	<2%
Repeatability (with dither)	<2%
Recommended dither frequency	140 Hz
Deadband, nominal (as a percentage of input)	30%
Series	1
Capacity	34 L/min.
Manual Override Force Requirement	33 N/100 bar @ Port 1
Manual Override Stroke	2,5 mm
Maximum Valve Leakage at 110 SUS (24 cSt)	30 cc/min.@70 bar
Solenoid Tube Diameter	19 mm
Valve Hex Size	22,2 mm
Valve Installation Torque	41 - 47 Nm
Model Weight (with coil)	0,50 kg
Seal and nut kit - Coil	Viton: 990-770-006
Seal kit - Cartridge	Buna: 990-411-007
Seal kit - Cartridge	Viton: 990-411-006

OPTION SELECTION EXAMPLE: FMDXCDN

CONTROL	(X)	FLOW RATE	(C)	SEAL MATERIAL	(N)	BOBINA
X No Manual Override		C .1 - 6 gpm (0,4 - 23 L/min.)		N Buna-N		No coil
D Twist/Lock (Dual) Manual Override		A .1 - 1.6 gpm (0,4 - 6.1 L/min.)		E EPDM		224NX01 DIN 43650-Form A, 24 VDC, no transient voltage suppression (TVS) diodes, with XMD-01 driver
E Twist (Extended) Manual Override		B .1 - 4 gpm (0,4 - 15 L/min.)		V Viton		224NX02 DIN 43650-Form A, 24 VDC, no transient voltage suppression (TVS) diodes, with XMD-02 driver
L Twist/Lock (Detent) Manual Override		D .1 - 9 gpm (0,4 - 34 L/min.)				912NX01 Deutsch DT04-2P, 12 VDC, no transient voltage suppression (TVS) diodes, with XMD-01 driver
M activador manual						912NX02 Deutsch DT04-2P, 12 VDC, no transient voltage suppression (TVS) diodes, with XMD-02 driver
T Twist (Momentary) Manual Override						924NX01 Deutsch DT04-2P, 24 VDC, no transient voltage suppression (TVS) diodes, with XMD-01 driver
						924NX02 Deutsch DT04-2P, 24 VDC, no transient voltage suppression (TVS) diodes, with XMD-02 driver

PERFORMANCE CURVES

