



*An additional 2.00 (50,8) clearance needed for coil installation and removal

3 1 2 3 1 2

PROPORTIONAL PERFORMANCE DATA

	<4%
	<8%
	<2%
()	<2%
	140 Hz

TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-11A
	1
	34 L/min.
	350 bar
110 SUS (24 cSt)	30 cc/min. @70 bar
	2,5 mm
	33 N/100 bar @ Port 1
	16 mm
	22,2 mm
	41 - 47 Nm

- Sun
- 2.00 inches (50,8 mm)

OPTION SELECTION EXAMPLE: FMDFXCDN

	(X)	(C)	(N)
X		C .1 - 6 gpm (0,4 - 23 L/min.)	N
D /		A .1 - 1.6 gpm (0,4 - 6.1 L/min.)	V
L		B .1 - 4 gpm (0,4 - 15 L/min.)	
M		D .1 - 9 gpm (0,4 - 34 L/min.)	
T ()			

TECHNICAL FEATURES

- 2 3 1.5gpm 5L/min
-
- 2 3 4
- LR*C-XHN LP*C-XHN
-
- 100-250Hz
- Sun

PERFORMANCE CURVES



