



3 4 AB T A 3 P 2 B 4 A 1 T

PROPORTIONAL PERFORMANCE DATA

<20%
A & V spool: 160 Hz, C & X spool: 220 Hz, E & Z spool: 320 Hz
<8%

TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	SC-10-04
	1C
	40 L/min.
	250 bar
110 SUS (24 cSt)	110 mL/min.@3600 psi
	50 ms
	19 mm
	4,8 - 5,3 Nm
	25,4 mm
	38 - 43 Nm
(T)	5,7 - 6,2 Nm
	0,55 kg

OPTION SELECTION EXAMPLE: FNUCXEN

	(X)	(E)	(N)
X	E	E	N
T ()	A 1.3 gpm (4,8 L/min.)		
	C 4 gpm (15 L/min.)		
	V 1.3 gpm A B (4,8 L/min.)		
	X 4 gpm A B (15 L/min.)		
	Z 8 gpm A B (30 L/min.)		

TECHNICAL FEATURES

-
-
-
- 1 1000 psi (70 bar) 3600 psi (250 bar)
- 3
-
-
- 2 LPDC 3 LRDC
-
- 12V (778212 and 778912D) 100%
- (T) 1 1000 psi (70 bar) 3 4 2 1 3 2 4
- SC-10-04 SUN (: JPA).
-
- IP67
- 30 lbf ft (40 Nm)

PERFORMANCE CURVES



