



2 1 1 2

**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-162A
	0
	20 L/min.
	350 bar
	15%
	3%
( )	3%
	140 Hz
110 SUS (24 cSt)	0,07 cc/min. @210 bar
	7 bar
	48%
	2,8 - 380 cSt
	50 ms
	15,000 max. cycles/hr
	19,1 mm
	27 - 33 Nm
	0.23 kg.
Seal kit - Cartridge	Buna: 990-162-007
Seal kit - Cartridge	Viton: 990-162-006
Seal kit - Cartridge	Buna: 990-162-007
Seal kit - Cartridge	Viton: 990-162-006

- : • Sun
- 2.00 inches (50,8 mm)

# OPTION SELECTION EXAMPLE: FPBFXDN

(X)	(D)	(N)
X	D 5 gpm @ 200 psi (14 bar) (20 L/min.)	N V

## TECHNICAL FEATURES

- 200 psi (14 bar)
- FLeX Sun XMD
- 1000
- NFPA T2.6.1 R2014
- 
- CFD
- 100-250Hz
- FPB\*
- 1000
- FLeX
- 
- IP69K
- 
- Sun

## PERFORMANCE CURVES

