



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

110 SUS (24 cSt)	100 cc/min. @210 bar
	2,5 mm
	33 N/100 bar @ Port 1
Seal kit - Cartridge	Buna: 990-413-007
Seal kit - Cartridge	EPDM: 990-010-014
Seal kit - Cartridge	Polyurethane: 990-413-002
Seal kit - Cartridge	Viton: 990-413-006

: • Sun

CONFIGURATION OPTIONS

Model Code Example: FPCCXCN

(X)	(C)	(N)	(N)
X	C .25 - 7 gpm (1 - 28 L/min.)	N	
D /	A .1 - 1.5 gpm (0,4 - 6 L/min.)	E EPDM	224NX01 DIN 43650 A 24 VDC (TVS) XMD-01
E ()	B .15 - 3.5 gpm (0,6 - 14 L/min.)	V	224NX02 DIN 43650 A 24 VDC (TVS) XMD-02
L	D .25 - 10 gpm (1 - 40 L/min.)		912NX01 Deutsch DT04-2P 12 VDC (TVS) XMD-01
M			912NX02 Deutsch DT04-2P 12 VDC (TVS) XMD-02
T ()			924NX01 Deutsch DT04-2P 24 VDC (TVS) XMD-01
			924NX02 Deutsch DT04-2P 24 VDC (TVS) XMD-02