



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

110 SUS (24 cSt)	100 cc/min.@210 bar
	2,5 mm
	33 N/100 bar @ Port 1

: • Sun

CONFIGURATION OPTIONS

Model Code Example: **FPCCXCN**

(X)	(C)	(N)	
X	C .25 - 7 gpm (1 - 28 L/min.)	N	
D /	A .1 - 1.5 gpm (0,4 - 6 L/min.)	E EPDM	212 DIN 43650 A 12 VDC
E ()	B .15 - 3.5 gpm (0,6 - 14 L/min.)	V	224 DIN 43650 A 24 VDC
L	D .25 - 10 gpm (1 - 40 L/min.)		224NX01 DIN 43650 A 24 VDC (TVS) XMD-01
M			224NX02 DIN 43650 A 24 VDC (TVS) XMD-02
T ()			912 Deutsch DT04-2P 12 VDC
			912NX01 Deutsch DT04-2P 12 VDC (TVS) XMD-01
			912NX02 Deutsch DT04-2P 12 VDC (TVS) XMD-02
			924 Deutsch DT04-2P 24 VDC
			924NX01 Deutsch DT04-2P 24 VDC (TVS) XMD-01
			924NX02 Deutsch DT04-2P 24 VDC (TVS) XMD-02