



**CONFIGURATION**

X	
C	.25 - 7 gpm (1 - 28 L/min.)
N	

**TECHNICAL DATA**

110 SUS (24 cSt)	100 cc/min. @ 210 bar
	2,5 mm
	33 N/100 bar @ Port 1

: • Sun

**CONFIGURATION OPTIONS**

Model Code Example: FPCHXCN

(X)	(C)	(N)	(914NX01)
<b>X</b>	<b>C</b> .25 - 7 gpm (1 - 28 L/min.)	<b>N</b>	
D /	A .1 - 1.5 gpm (0,4 - 6 L/min.)	E EPDM	<b>224NX01</b> DIN 43650 A 24 VDC (TVS) XMD-01
E ( )	B .15 - 3.5 gpm (0,6 - 14 L/min.)	V	<b>224NX02</b> DIN 43650 A 24 VDC (TVS) XMD-02
L			<b>912NX01</b> Deutsch DT04-2P 12 VDC (TVS) XMD-01
M			<b>912NX02</b> Deutsch DT04-2P 12 VDC (TVS) XMD-02
T ( )			<b>924NX01</b> Deutsch DT04-2P 24 VDC (TVS) XMD-01
			<b>924NX02</b> Deutsch DT04-2P 24 VDC (TVS) XMD-02