



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Seal kit - Cartridge	Buna: 990-016-007
Seal kit - Cartridge	EPDM: 990-016-014
Seal kit - Cartridge	Polyurethane: 990-016-002
Seal kit - Cartridge	Viton: 990-016-006

**CONFIGURATION OPTIONS**

**Model Code Example: FPHKXCN**

CONTROL	(X)	FLOW RATE	(C)	SEAL MATERIAL	(N)	BOBINA
<b>X</b> No Manual Override		<b>C</b> Nominal 40 gpm @ 200 psi (14 bar) differential (160 L/min.)		<b>N</b> Buna-N		No coil
<b>E</b> Twist (Extended) Manual Override		<b>A</b> Nominal 20 gpm @ 200 psi (14 bar) differential (80 L/min.)		<b>E</b> EPDM		<b>224NX01</b> DIN 43650-Form A, 24 VDC, no transient voltage suppression (TVS) diodes, with XMD-01 driver
<b>M</b> activador manual		<b>E</b> Nominal 60 gpm @ 200 psi (14 bar) differential (240 L/min.)		<b>V</b> Viton		<b>224NX02</b> DIN 43650-Form A, 24 VDC, no transient voltage suppression (TVS) diodes, with XMD-02 driver
						<b>912NX01</b> Deutsch DT04-2P, 12 VDC, no transient voltage suppression (TVS) diodes, with XMD-01 driver
						<b>912NX02</b> Deutsch DT04-2P, 12 VDC, no transient voltage suppression (TVS) diodes, with XMD-02 driver
						<b>924NX01</b> Deutsch DT04-2P, 24 VDC, no transient voltage suppression (TVS) diodes, with XMD-01 driver
						<b>924NX02</b> Deutsch DT04-2P, 24 VDC, no transient voltage suppression (TVS) diodes, with XMD-02 driver