



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

|   |                           |
|---|---------------------------|
| cavidad                                   | T-162A                    |
| Series                                    | 0                         |
| Capacity                                  | 8,5 L/min.                |
| Maximum Operating Pressure                | 350 bar                   |
| Maximum Valve Leakage at 110 SUS (24 cSt) | 15 cc/min.@70 bar         |
| Valve Hex Size                            | 19,1 mm                   |
| Valve Installation Torque                 | 27 - 33 Nm                |
| Seal kit - Cartridge                      | Buna: 990-162-007         |
| Seal kit - Cartridge                      | EPDM: 990-162-014         |
| Seal kit - Cartridge                      | Polyurethane: 990-162-002 |
| Seal kit - Cartridge                      | Viton: 990-162-006        |

## OPTION SELECTION EXAMPLE: FQBAXAN

| CONTROL          | (X) SETTING RANGE                                       | (A) SEAL MATERIAL             | (N) MATERIAL/COATING  |
|------------------|---|-------------------------------|---|
| X Not Adjustable | A Replaceable Orifice .5 - 2.25 gpm<br>(2 - 8,5 L/min.) | N Buna-N<br>E EPDM<br>V Viton | Standard Material/Coating<br>/AP Stainless Steel, Passivated<br>/LH Mild Steel, Zinc-Nickel |

### PERFORMANCE CURVES

