



CONFIGURATION

L	
A	.1 - 12 gpm (0,4 - 45 L/min.)
N	
Material/Coating	

TECHNICAL DATA

NOTE:

	T-2A	DATA
	2	MAY
	45 L/min.	VARY
	350 bar	BY
	120 L/min.	
	28,6 mm	
	61 - 68 Nm	
	4 mm	
	15 mm	
	9 - 10 Nm	
	0.28 kg.	
Seal kit - Cartridge	Buna: 990-202-007	
Seal kit - Cartridge	EPDM: 990-202-014	
Seal kit - Cartridge	Polyurethane: 990-002-002	
Seal kit - Cartridge	Viton: 990-202-006	

: • O 1 0.75 in. (19 mm)

CONFIGURATION. SEE CONFIGURATION SECTION.

OPTION SELECTION EXAMPLE: FRDALAN

	(L)	(A)	(N)	MATERIAL/COATING
L		A .1 - 12 gpm (0,4 - 45 L/min.)	N	Standard Material/Coating
C -		B .1 - 12 gpm (0,4 - 45 L/min.)	E EPDM	/AP
X			V	

TECHNICAL FEATURES

- +/- 10%
- 3 3000 psi (210 bar)
-
-
-
- 2 3
-
- +/- 25% +/- 3
- Sun /
- EPDM EPDM

PERFORMANCE CURVES

