



PORT 1
CONTROLLED FLOW INLET

CONFIGURATION

X Control	Not Adjustable
A Setting Range	Replaceable Orifice .1 - 12 gpm (0,4 - 45 L/min.)
N Seal Material	Buna-N
	Material/Coating

Bypass/restrictive, fixed-orifice, priority flow controls take an input flow at port 1 and use it to satisfy the priority flow at port 3. If the input flow exceeds the priority flow requirement, the excess is bypassed out port 2. The bypass flow may be used in a secondary circuit.

TECHNICAL DATA

Maximum Operating Pressure	5000 psi
Maximum Input Flow	30 gpm
Locknut Hex Size	9/16 in.
Locknut Torque	80 - 90 lbf in.
Seal kit - Cartridge	Buna: 990-202-007
Seal kit - Cartridge	EPDM: 990-202-014
Seal kit - Cartridge	Polyurethane: 990-002-002
Seal kit - Cartridge	Viton: 990-202-006

NOTES: • For Series 1 cartridges configured with an O control (panel mount handknob), a .75 in. (19 mm) diameter hole is required in the panel.

CONFIGURATION OPTIONS

Model Code Example: **FRDAXAN**

CONTROL	(X)	SETTING RANGE	(A)	SEAL MATERIAL	(N)	MATERIAL/COATING
X Not Adjustable		A Replaceable Orifice .1 - 12 gpm (0,4 - 45 L/min.)		N Buna-N		Standard Material/Coating
C Tamper Resistant - Factory Set		B Permanent Orifice .1 - 12 gpm (0,4 - 45 L/min.)		E EPDM		IAP Stainless Steel, Passivated
L Tuning Adjustment				V Viton		