



Port 1
Controlled Flow Inlet

Port 3
Priority
Flow

Port 2
Bypass
Flow

TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Maximum Input Flow	240 L/min.
Locknut Hex Size	15 mm
Locknut Torque	9 - 10 Nm
Seal kit - Cartridge	Buna: 990-017-007
Seal kit - Cartridge	Polyurethane: 990-017-002
Seal kit - Cartridge	Viton: 990-017-006
Seal kit - Cartridge	Buna: 990-017-007
Seal kit - Cartridge	Polyurethane: 990-017-002
Seal kit - Cartridge	Viton: 990-017-006

CONFIGURATION OPTIONS

Model Code Example: FREAXAN

CONTROL	(X)	SETTING RANGE	(A)	SEAL MATERIAL	(N)	MATERIAL/COATING
X Not Adjustable		A Replaceable Orifice .2 - 25 gpm (0,8 - 95 L/min.)		N Buna-N		Standard Material/Coating
C Tamper Resistant - Factory Set		B Permanent Orifice .2 - 25 gpm (0,8 - 95 L/min.)		V Viton		/AP Stainless Steel, Passivated
K manilla						/LH Mild Steel, Zinc-Nickel
L Tuning Adjustment						