



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Typical Valve Leakage at 110 SUS (24 cSt) from port 1 to port 3 at 1450 psi (100 bar)	30 mL/min.
Typical Valve Leakage at 110 SUS (24 cSt) from port 1 to port 3 at 5000 psi (350 bar)	110 mL/min.
Viscosity Range	2,8 - 380 cSt
Response Time - Typical	50 ms
Switching Frequency	3,600 max. cycles/hr
Seal kit - Cartridge	Buna: 990-017-007
Seal kit - Cartridge	Viton: 990-017-006
U.S. Patent #	10,969,033

**CONFIGURATION OPTIONS**

**Model Code Example: FREPXAN**

CONTROL	(X)	FLOW RATE	(A)	SEAL MATERIAL	(N)	BOBINA
<b>X</b> No Manual Override		<b>A</b> Nominal 8 gpm (30 L/min.)		<b>N</b> Buna-N		No coil
<b>P</b> Manual Pull Override		<b>B</b> Nominal 16 gpm (60 L/min.)		<b>V</b> Viton		
		<b>C</b> Nominal 22 gpm (88 L/min.)				