



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

| | |
|------------------------------------|---------------------------|
| cavidad | T-19A |
| Series | 4 |
| Capacity | 200 L/min. |
| Maximum Operating Pressure | 350 bar |
| Maximum Input Flow | 480 L/min. |
| Valve Hex Size | 41,3 mm |
| Valve Installation Torque | 474 - 508 Nm |
| Adjustment Screw Internal Hex Size | 4 mm |
| Locknut Hex Size | 15 mm |
| Locknut Torque | 9 - 10 Nm |
| Model Weight | 1.03 kg. |
| Seal kit - Cartridge | Buna: 990-019-007 |
| Seal kit - Cartridge | Polyurethane: 990-019-002 |
| Seal kit - Cartridge | Viton: 990-019-006 |
| Seal kit - Cartridge | Buna: 990-019-007 |
| Seal kit - Cartridge | Polyurethane: 990-019-002 |
| Seal kit - Cartridge | Viton: 990-019-006 |

OPTION SELECTION EXAMPLE: FRFAXAN

| CONTROL | (X) SETTING RANGE | (A) SEAL MATERIAL | (N) |
|----------------------------------|--|-------------------|-----|
| X Not Adjustable | A Replaceable Orifice .2 - 50 gpm (1 - 200 L/min.) | N Buna-N | |
| C Tamper Resistant - Factory Set | B Permanent Orifice .2 - 50 gpm (1 - 200 L/min.) | V Viton | |
| K manilla | | | |
| L Tuning Adjustment | | | |

PERFORMANCE CURVES

