



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Divisional Accuracy at Max Input Flow	±2.5%
Divisional Accuracy at Minimum Input Flow	±4.5%
Pressure Drop at Maximum Rated Input Flow	18 bar
Pressure Drop at Minimum Rated Input Flow	2 bar
Rated Input Flow with 33/67 Split	1,7 - 8,5 L/min.
Rated Input Flow with 40/60 Split	2,8 - 9,5 L/min.
Rated Input Flow with 50/50 Split	2,5 - 12 L/min.
Seal kit - Cartridge	Buna: 990-031-007
Seal kit - Cartridge	Polyurethane: 990-031-002
Seal kit - Cartridge	Viton: 990-031-006
Seal kit - Cartridge	Buna: 990-031-007
Seal kit - Cartridge	Polyurethane: 990-031-002
Seal kit - Cartridge	Viton: 990-031-006

CONFIGURATION OPTIONS

Model Code Example: FSBDXAN

CONTROL

(X)

FLOW SPLIT

(A)

SEAL MATERIAL

(N)

MATERIAL/COATING

X Not Adjustable

A 50/50

N Buna-N

Standard Material/Coating

B 40/60

V Viton

/AP Stainless Steel, Passivated

C 33/67