



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Divisional Accuracy at Max Input Flow	±3.5%
Divisional Accuracy at Minimum Input Flow	±6.5%
Pressure Drop at Maximum Rated Input Flow	18 bar
Pressure Drop at Minimum Rated Input Flow	2 bar
Rated Input Flow with 33/67 Split	4,5 - 22,7 L/min.
Rated Input Flow with 40/60 Split	5,3 - 26,5 L/min.
Rated Input Flow with 50/50 Split	6 - 30 L/min.
Seal kit - Cartridge	Buna: 990-031-007
Seal kit - Cartridge	Polyurethane: 990-031-002
Seal kit - Cartridge	Viton: 990-031-006
Seal kit - Cartridge	Buna: 990-031-007
Seal kit - Cartridge	Polyurethane: 990-031-002
Seal kit - Cartridge	Viton: 990-031-006

CONFIGURATION OPTIONS

Model Code Example: **FSCDXAN**

CONTROL	(X)	FLOW SPLIT	(A)	SEAL MATERIAL	(N)	MATERIAL/COATING
X Not Adjustable		A 50/50		N Buna-N		Standard Material/Coating
		B 40/60		V Viton		/AP Stainless Steel, Passivated
		C 33/67				/LH Mild Steel, Zinc-Nickel