



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Divisional Accuracy at Max Input Flow	50% ±2.5%
Divisional Accuracy at Minimum Input Flow	50% ±4.5%
Pressure Drop at Maximum Rated Input Flow	24 bar
Pressure Drop at Minimum Rated Input Flow	2 bar
Seal kit - Cartridge	Buna: 990-032-007
Seal kit - Cartridge	EPDM: 990-032-014
Seal kit - Cartridge	Polyurethane: 990-032-002
Seal kit - Cartridge	Viton: 990-032-006
Seal kit - Cartridge	Buna: 990-032-007
Seal kit - Cartridge	EPDM: 990-032-014
Seal kit - Cartridge	Polyurethane: 990-032-002
Seal kit - Cartridge	Viton: 990-032-006

CONFIGURATION OPTIONS

Model Code Example: **FSDAXAN**

CONTROL	(X)	FLOW SPLIT	(A)	SEAL MATERIAL	(N)	MATERIAL/COATING
X Not Adjustable		A 50/50		N Buna-N		Standard Material/Coating
				E EPDM		IAP Stainless Steel, Passivated
				V Viton		