



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-32A
	2
	6 - 30 L/min.
	18 bar
	2 bar
	28,6 mm
	61 - 68 Nm
	0.26 kg.
Seal kit - Cartridge	Buna: 990-032-007
Seal kit - Cartridge	Polyurethane: 990-032-002
Seal kit - Cartridge	Viton: 990-032-006
Seal kit - Cartridge	Buna: 990-032-007
Seal kit - Cartridge	Polyurethane: 990-032-002
Seal kit - Cartridge	Viton: 990-032-006

OPTION SELECTION EXAMPLE: FSDCXAN

	(X)	(A)	(N)	MATERIAL/COATING
X	A	50/50	N	Standard Material/Coating
			V	/AP

TECHNICAL FEATURES

- /
-
-
-
-
-
-
-
-
- Sun

0

PERFORMANCE CURVES

Split	Input Flow		Rated Accuracy	Maximum Possible Flow Variation
	Max	Rated		
50:50	8 gpm	30 L/min	±2%	3.84 - 4.16 gpm
				14.4 - 15.6 L/min
	1.5 gpm	6.0 L/min	±3%	.70 - .80 gpm
				2.8 - 3.2 L/min

The maximum possible variation is at 5000 psi (350 bar) differential between legs with the high pressure leg being the higher flow.