



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

|   |                           |
|---|---------------------------|
| Maximum Operating Pressure                | 350 bar                   |
| Divisional Accuracy at Max Input Flow     | ±3.5%                     |
| Divisional Accuracy at Minimum Input Flow | ±6.5%                     |
| Pressure Drop at Maximum Rated Input Flow | 18 bar                    |
| Pressure Drop at Minimum Rated Input Flow | 2 bar                     |
| Rated Input Flow with 33/67 Split         | 8,4 - 42 L/min.           |
| Rated Input Flow with 40/60 Split         | 9,4 - 47 L/min.           |
| Rated Input Flow with 50/50 Split         | 12 - 60 L/min.            |
| Seal kit - Cartridge                      | Buna: 990-032-007         |
| Seal kit - Cartridge                      | Polyurethane: 990-032-002 |
| Seal kit - Cartridge                      | Viton: 990-032-006        |
| Seal kit - Cartridge                      | Buna: 990-032-007         |
| Seal kit - Cartridge                      | Polyurethane: 990-032-002 |
| Seal kit - Cartridge                      | Viton: 990-032-006        |

**CONFIGURATION OPTIONS**

Model Code Example: **FSDDXAN**

| CONTROL                 | (X) | FLOW SPLIT     | (A) | SEAL MATERIAL   | (N) | MATERIAL/COATING                       |
|-------------------------|-----|----------------|-----|-----------------|-----|--|
| <b>X</b> Not Adjustable |     | <b>A</b> 50/50 |     | <b>N</b> Buna-N |     | Standard Material/Coating              |
|                         |     | <b>B</b> 40/60 |     | <b>V</b> Viton  |     | <b>IAP</b> Stainless Steel, Passivated |
|                         |     | <b>C</b> 33/67 |     |                 |     |  |
|                         |     | <b>D</b> 25/75 |     |                 |     |  |