



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-32A
	2
	6 - 30 L/min.
	350 bar
	50% ±2.0%
	24 bar
	50% ±3.0%
	2 bar
	28,6 mm
	61 - 68 Nm
	0.27 kg.
Seal kit - Cartridge	Buna: 990-032-007
Seal kit - Cartridge	Polyurethane: 990-032-002
Seal kit - Cartridge	Viton: 990-032-006
Seal kit - Cartridge	Buna: 990-032-007
Seal kit - Cartridge	Polyurethane: 990-032-002
Seal kit - Cartridge	Viton: 990-032-006

## OPTION SELECTION EXAMPLE: FSDRXAN

(X)	(A)	(N)	MATERIAL/COATING
X	A 50/50	N V	Standard Material/Coating /AP

### TECHNICAL FEATURES

- /
- 
- 
- 
- 
- 
- 
- 
- 
- 15%
- 3
- 0
- Sun

### PERFORMANCE CURVES

Split	Input Flow		Rated Accuracy	Maximum Possible Flow Variation
<b>50:50</b>	Max	8 gpm	±2%	3.84 - 4.16 gpm
	Rated	30 L/min		14.4 - 15.6 L/min
	Min	1.5 gpm	±3%	.70 - .80 gpm
	rated	6 L/min		2.8 - 3.2 L/min
<b>Synchronizing Flow</b>				.30 - .75 gpm 1.1 - 2.8 L/min

The maximum possible variation is at 5000 psi (350 bar) differential between legs with the high pressure leg being the higher flow in dividing and the lower flow in combining.