



Port 4 Outlet      Port 3 Inlet      Port 2 Outlet

**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-33A
	3
	12 - 60 L/min.
	18 bar
	2 bar
	31,8 mm
	203 - 217 Nm
	0.61 kg.
Seal kit - Cartridge	Buna: 990-033-007
Seal kit - Cartridge	Polyurethane: 990-033-002
Seal kit - Cartridge	Viton: 990-033-006
Seal kit - Cartridge	Buna: 990-033-007
Seal kit - Cartridge	Polyurethane: 990-033-002
Seal kit - Cartridge	Viton: 990-033-006

## OPTION SELECTION EXAMPLE: FSECXAN

	(X)	(A)	(N)	MATERIAL/COATING
X	A	50/50	N	Standard Material/Coating
		V		/AP

### TECHNICAL FEATURES

- /
- 
- 
- 
- 
- 
- 
- 
- 
- Sun 0

### PERFORMANCE CURVES

Split	Input Flow		Rated Accuracy	Maximum Possible Flow Variation
50:50	Max Rated	15 gpm	±2%	7.2 - 7.8 gpm
		60 L/min		28,8 - 31,2 L/min
	Min rated	3 gpm	±3%	1.41 - 1.59 gpm
		12 L/min		5,6 - 6,4 L/min

The maximum possible variation is at 5000 psi (350 bar) differential between legs with the high pressure leg being the higher flow.