



Flow dividers are sliding-spool, pressure-compensated devices used to split oil flow to two different branches of a circuit in a designated ratio. These valves are suitable for applications that use the following: unidirectional hydraulic motors, hydraulic cylinders where flow division in one direction only is required, and multiple circuits that are serviced from one pump supply.

TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	5000 psi
Divisional Accuracy at Max Input Flow	±3.5%
Divisional Accuracy at Minimum Input Flow	±6.5%
Pressure Drop at Maximum Rated Input Flow	250 psi
Pressure Drop at Minimum Rated Input Flow	30 psi
Rated Input Flow with 33/67 Split	4.4 - 22 gpm
Rated Input Flow with 40/60 Split	5 - 25 gpm
Rated Input Flow with 50/50 Split	6 - 30 gpm
Seal kit - Cartridge	Buna: 990-033-007
Seal kit - Cartridge	Polyurethane: 990-033-002
Seal kit - Cartridge	Viton: 990-033-006

CONFIGURATION OPTIONS

Model Code Example: **FSEDXAN**

CONTROL	(X)	FLOW SPLIT	(A)	SEAL MATERIAL	(N)	MATERIAL/COATING
X Not Adjustable		A 50/50		N Buna-N		Standard Material/Coating
		B 40/60		E EPDM		JAP Stainless Steel, Passivated
		C 33/67		V Viton		