



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-34A
Series	4
Capacity	23 - 120 L/min.
Pressure Drop at Maximum Rated Input Flow	18 bar
Pressure Drop at Minimum Rated Input Flow	2 bar
Valve Hex Size	41,3 mm
Valve Installation Torque	474 - 508 Nm
Model Weight	1.28 kg.
Seal kit - Cartridge	Buna: 990-034-007
Seal kit - Cartridge	Polyurethane: 990-034-002
Seal kit - Cartridge	Viton: 990-034-006
Seal kit - Cartridge	Buna: 990-034-007
Seal kit - Cartridge	Polyurethane: 990-034-002
Seal kit - Cartridge	Viton: 990-034-006

## OPTION SELECTION EXAMPLE: FSFCXAN

CONTROL

(X) FLOW SPLIT

(A) SEAL MATERIAL

(N)

**X** Not Adjustable

**A** 50/50

**N** Buna-N

V Viton

### PERFORMANCE CURVES

Split	Input Flow		Rated Accuracy	Maximum Possible Flow Variation	Split	Input Flow		Rated Accuracy	Maximum Possible Flow Variation
	Max	Rated				Max	Rated		
50:50	Max	30 gpm	±2.0%	14.4 - 15.6 gpm	50:50	Max	30 gpm	±2.0%	14.4 - 15.6 gpm
		120 L/min		57,6 - 62,4 L/min			120 L/min		57,6 - 62,4 L/min
	Min rated	6 gpm	±3.0%	2.8 - 3.2 gpm		Min rated	6 gpm	±3.0%	2.8 - 3.2 gpm
		24 L/min		11,3 - 12,7 L/min			24 L/min		11,3 - 12,7 L/min

The maximum possible variation is at 5000 psi (350 bar) differential between legs with the high pressure leg being the higher flow.

The maximum possible variation is at 5000 psi (350 bar) differential between legs with the high pressure leg being the higher flow.