



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-34A
	4
	23 - 120 L/min.
	18 bar
	2 bar
	41,3 mm
	474 - 508 Nm
	1.28 kg.
Seal kit - Cartridge	Buna: 990-034-007
Seal kit - Cartridge	Polyurethane: 990-034-002
Seal kit - Cartridge	Viton: 990-034-006
Seal kit - Cartridge	Buna: 990-034-007
Seal kit - Cartridge	Polyurethane: 990-034-002
Seal kit - Cartridge	Viton: 990-034-006

OPTION SELECTION EXAMPLE: FSFCXAN

(X)

(A)

(N)

X

A 50/50

N

V

TECHNICAL FEATURES

- /
-
-
-
-
-
-
-
- Sun

0

PERFORMANCE CURVES

Split	Input Flow		Rated Accuracy	Maximum Possible Flow Variation	Split	Input Flow		Rated Accuracy	Maximum Possible Flow Variation
	Max	Rated				Max	Rated		
50:50	Max	30 gpm	±2.0%	14.4 - 15.6 gpm	50:50	Max	30 gpm	±2.0%	14.4 - 15.6 gpm
	Rated	120 L/min		57.6 - 62.4 L/min		Rated	120 L/min		57.6 - 62.4 L/min
	Min rated	6 gpm	±3.0%	2.8 - 3.2 gpm		Min rated	6 gpm	±3.0%	2.8 - 3.2 gpm
		24 L/min		11.3 - 12.7 L/min			24 L/min		11.3 - 12.7 L/min

The maximum possible variation is at 5000 psi (350 bar) differential between legs with the high pressure leg being the higher flow.

The maximum possible variation is at 5000 psi (350 bar) differential between legs with the high pressure leg being the higher flow.