



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Divisional Accuracy at Max Input Flow	±3.5%
Divisional Accuracy at Minimum Input Flow	±6.5%
Pressure Drop at Maximum Rated Input Flow	18 bar
Pressure Drop at Minimum Rated Input Flow	2 bar
Rated Input Flow with 33/67 Split	36 - 180 L/min.
Rated Input Flow with 40/60 Split	38 - 200 L/min.
Rated Input Flow with 50/50 Split	45 - 240 L/min.
Seal kit - Cartridge	Buna: 990-034-007
Seal kit - Cartridge	Polyurethane: 990-034-002
Seal kit - Cartridge	Viton: 990-034-006
Seal kit - Cartridge	Buna: 990-034-007
Seal kit - Cartridge	Polyurethane: 990-034-002
Seal kit - Cartridge	Viton: 990-034-006

**CONFIGURATION OPTIONS**

**Model Code Example: FSFDXAN**

CONTROL	(X)	FLOW SPLIT	(A)	SEAL MATERIAL	(N)	MATERIAL/COATING
<b>X</b> Not Adjustable		<b>A</b> 50/50		<b>N</b> Buna-N		Standard Material/Coating
		<b>B</b> 40/60		<b>V</b> Viton		<b>/AP</b> Stainless Steel, Passivated
		<b>C</b> 33/67				<b>/LH</b> Mild Steel, Zinc-Nickel
		<b>D</b> 25/75				