



2 2 . 2 3 4 5 1 2 3 4 5 1

### SWITCH SPECIFICATIONS

	20-30 VDC
	-25 to 80 °C
	≥ 50g, 0-500 impulses/sec
	>50 g, 1ms
	≤ 400 mA, Duty Ratio 100%
	Yes, Load Short Unlimited
	≤ 25 ms
	35 %
- 0-80 °C ≤ ±	0,1 mm
	DIN EN 61000-6-1/2/3/4
	M12 X 1 (4) Pin
	IP65
Seal kit - Cartridge	Buna: 990-152-007
Seal kit - Cartridge	Viton: 990-152-006

### TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-52AD
	2
	120 L/min.
	350 bar
	3,5 - 8 bar
	20 - 23 bar
	0,82 cc
110 SUS (24 cSt)	80 cc/min.@70 bar
	28,6 mm
	61 - 68 Nm
Seal kit - Cartridge	Buna: 990-152-007
Seal kit - Cartridge	Viton: 990-152-006

# OPTION SELECTION EXAMPLE: FTDAZCN

(C)

(N)

C

N

V

## TECHNICAL FEATURES

- 
- CE
- 
- LR\*C-XHN                      LP\*C-XHN
- 
- 991-043
- 1 4                      500psi 35bar
- 4                      1
- Sun

## PERFORMANCE CURVES

