



2 2 . 1 2 3 1 2 3

SWITCH SPECIFICATIONS

	20-30 VDC
	-25 to 80 °C
	≥ 50g, 0-500 impulses/sec
	>50 g, 1ms
	≤ 400 mA, Duty Ratio 100%
	Yes, Load Short Unlimited
	≤ 25 ms
	35 %
- 0-80 °C ≤ ±	0,1 mm
	DIN EN 61000-6-1/2/3/4
	M12 X 1 (4) Pin
	IP65
Seal kit - Cartridge	Buna: 990-053-007
Seal kit - Cartridge	Viton: 990-053-006

TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-53AD
	3
	95 L/min.
	350 bar
	3,5 - 8 bar
	20 - 23 bar
	1,6 cc
110 SUS (24 cSt)	160 cc/min. @70 bar
	31,8 mm
	203 - 217 Nm
	1.70 kg.
Seal kit - Cartridge	Buna: 990-053-007
Seal kit - Cartridge	Viton: 990-053-006

OPTION SELECTION EXAMPLE: FTEAZCN

(C)

(N)

C

N

H

V

TECHNICAL FEATURES

-
- CE
-
- LR*C-XHN LP*C-XHN
-
-
- 991-043
- 1 4 500psi 35bar
- 4 1
- Sun

PERFORMANCE CURVES

