



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-22A
Series	2
Capacity	45 L/min.
Maximum Operating Pressure	350 bar
Maximum Input Flow	120 L/min.
Nominal Vent Flow	0,75 L/min.
Valve Hex Size	28,6 mm
Valve Installation Torque	61 - 68 Nm
Adjustment Screw Internal Hex Size	4 mm
Locknut Hex Size	15 mm
Locknut Torque	9 - 10 Nm
Model Weight	0.27 kg.
Seal kit - Cartridge	Buna: 990-022-007
Seal kit - Cartridge	EPDM: 990-022-014
Seal kit - Cartridge	Polyurethane: 990-022-002
Seal kit - Cartridge	Viton: 990-022-006

OPTION SELECTION EXAMPLE: FVDAXAN

CONTROL	(X)	SETTING RANGE	(A)	SEAL MATERIAL	(N)
X Not Adjustable		A Replaceable Orifice .1 - 12 gpm (0,4 - 45 L/min.)		N Buna-N	
L Tuning Adjustment		B Permanent Orifice .1 - 12 gpm (0,4 - 45 L/min.)		E EPDM	
				V Viton	

PERFORMANCE CURVES

