



CONFIGURATION

X	
A	.1 - 12 gpm (0,4 - 45 L/min.)
N	

/ 1 3

NOTE: DATA MAY VARY FROM TECHNICAL DATA SEE CONFIGURATION SECTION.

	T-22A
	2
	45 L/min.
	350 bar
	120 L/min.
	0,75 L/min.
	28,6 mm
	61 - 68 Nm
	4 mm
	15 mm
	9 - 10 Nm
	0.27 kg.
Seal kit - Cartridge	Buna: 990-022-007
Seal kit - Cartridge	EPDM: 990-022-014
Seal kit - Cartridge	Polyurethane: 990-022-002
Seal kit - Cartridge	Viton: 990-022-006

OPTION SELECTION EXAMPLE: FVDAXAN

	(X)	(A)	(N)
X	A	N	N
L	B	E	V
	.1 - 12 gpm (0,4 - 45 L/min.)		EPDM
	.1 - 12 gpm (0,4 - 45 L/min.)		

TECHNICAL FEATURES

- +/- 10%
- 4 3 2
- 3 3000 psi (210 bar)
-
-
-
- 4 1 150 psi (10,5 bar) 2
- 2 3
-
- +/- 25% +/- 3
- Sun /
- EPDM EPDM

PERFORMANCE CURVES

