


Image not found or type unknown



/

1

3

2

**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-23A
	3
	95 L/min.
	350 bar
	240 L/min.
	0,75 L/min.
	31,8 mm
	203 - 217 Nm
	4 mm
	15 mm
	9 - 10 Nm
	0.61 kg.
Seal kit - Cartridge	Buna: 990-023-007
Seal kit - Cartridge	Polyurethane: 990-023-002
Seal kit - Cartridge	Viton: 990-023-006
Seal kit - Cartridge	Buna: 990-023-007
Seal kit - Cartridge	Polyurethane: 990-023-002
Seal kit - Cartridge	Viton: 990-023-006

# OPTION SELECTION EXAMPLE: FVEAXAN

	(X)	(A)	(N)	MATERIAL/COATING
<b>X</b>	<b>A</b>	<b>.2 - 25 gpm (0,8 - 95 L/min.)</b>	<b>N</b>	<b>Standard Material/Coating</b>
L	B	.2 - 25 gpm (0,8 - 95 L/min.)	V	/LH -

## TECHNICAL FEATURES

- +/- 10%
- 4 3 2
- 3 3000 psi (210 bar)
- 
- 
- 4 1 150 psi (10,5 bar) 2
- 2 3
- 
- +/- 25% +/- 3
- Sun /

## PERFORMANCE CURVES

