



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Maximum Input Flow	480 L/min.
Nominal Vent Flow	0,75 L/min.
Locknut Hex Size	15 mm
Locknut Torque	9 - 10 Nm
Seal kit - Cartridge	Buna: 990-024-007
Seal kit - Cartridge	EPDM: 990-024-014
Seal kit - Cartridge	Polyurethane: 990-024-002
Seal kit - Cartridge	Viton: 990-024-006
Seal kit - Cartridge	Buna: 990-024-007
Seal kit - Cartridge	EPDM: 990-024-014
Seal kit - Cartridge	Polyurethane: 990-024-002
Seal kit - Cartridge	Viton: 990-024-006

CONFIGURATION OPTIONS

Model Code Example: FVFAXAN

CONTROL

(X)

SETTING RANGE

(A)

SEAL MATERIAL

(N)

X Not Adjustable

L Tuning Adjustment

A Replaceable Orifice .2 - 50 gpm (1 - 200 L/min.)

B Permanent Orifice .2 - 50 gpm (1 - 200 L/min.)

N Buna-N

E EPDM

V Viton