



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-24A
Series	4
Capacity	200 L/min.
Maximum Operating Pressure	350 bar
Maximum Input Flow	480 L/min.
Nominal Vent Flow	0,75 L/min.
Valve Hex Size	41,3 mm
Valve Installation Torque	474 - 508 Nm
Adjustment Screw Internal Hex Size	4 mm
Locknut Hex Size	15 mm
Locknut Torque	9 - 10 Nm
Model Weight	1,36 kg.
Seal kit - Cartridge	Buna: 990-024-007
Seal kit - Cartridge	EPDM: 990-024-014
Seal kit - Cartridge	Polyurethane: 990-024-002
Seal kit - Cartridge	Viton: 990-024-006

OPTION SELECTION EXAMPLE: FVFAXAN

CONTROL

(X)

SETTING RANGE

(A)

SEAL MATERIAL

(N)

- X** Not Adjustable
- L** Tuning Adjustment

- A** Replaceable Orifice .2 - 50 gpm (1 - 200 L/min.)
- B** Permanent Orifice .2 - 50 gpm (1 - 200 L/min.)

- N** Buna-N
- E** EPDM
- V** Viton

PERFORMANCE CURVES

