



CONFIGURATION

- X _____
- A _____ 2 - 50 gpm (1 - 200 L/min.)
- N _____

TECHNICAL DATA

NOTE:

	T-24A	DATA
	4	MAY
	200 L/min.	VARY
	350 bar	BY
	480 L/min.	
	0,75 L/min.	
	41,3 mm	
	474 - 508 Nm	
	4 mm	
	15 mm	
	9 - 10 Nm	
	1.36 kg.	
Seal kit - Cartridge	Buna: 990-024-007	
Seal kit - Cartridge	EPDM: 990-024-014	
Seal kit - Cartridge	Polyurethane: 990-024-002	
Seal kit - Cartridge	Viton: 990-024-006	

CONFIGURATION. SEE
CONFIGURATION SECTION.

OPTION SELECTION EXAMPLE: FVFAXAN

	(X)	(A)	(N)
X	A	N	
L	B	E	V
	.2 - 50 gpm (1 - 200 L/min.)	EPDM	
	.2 - 50 gpm (1 - 200 L/min.)		

TECHNICAL FEATURES

- +/- 10%
- 4 3 2
- 3 3000 psi (210 bar)
-
-
- 4 1 150 psi (10,5 bar) 2
- 2 3
-
- +/- 25% +/- 3
- Sun /
- EPDM EPDM

PERFORMANCE CURVES

