



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-24A
Series	4
Capacity	200 L/min.
Maximum Operating Pressure	350 bar
Maximum Input Flow	480 L/min.
Nominal Vent Flow	0,75 L/min.
Pilot Control Cavity	T-8A
Pilot Control Valve Hex Size	22,2 mm
Pilot Control Valve Installation Torque	27 - 33 Nm
Valve Hex Size	41,3 mm
Valve Installation Torque	474 - 508 Nm
Model Weight	1.33 kg.
Seal kit - Cartridge	Buna: 990-024-007
Seal kit - Cartridge	EPDM: 990-024-014
Seal kit - Cartridge	Polyurethane: 990-024-002
Seal kit - Cartridge	Viton: 990-024-006
Seal kit - Cartridge	Buna: 990-024-007
Seal kit - Cartridge	EPDM: 990-024-014
Seal kit - Cartridge	Polyurethane: 990-024-002
Seal kit - Cartridge	Viton: 990-024-006

# OPTION SELECTION EXAMPLE: FVFA8AN

SETTING RANGE

(A) SEAL MATERIAL

(N)

**A** Replaceable Orifice .2 - 50 gpm (1 - 200 L/min.)

**N** Buna-N

**B** Permanent Orifice .2 - 50 gpm (1 - 200 L/min.)

**E** EPDM

**V** Viton

## PERFORMANCE CURVES

