



/

T-8A

1

3

TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-24A
	4
	200 L/min.
	350 bar
	T-8A
	22,2 mm
	27 - 33 Nm
	480 L/min.
	0,75 L/min.
	41,3 mm
	474 - 508 Nm
	1.33 kg.
Seal kit - Cartridge	Buna: 990-024-007
Seal kit - Cartridge	EPDM: 990-024-014
Seal kit - Cartridge	Polyurethane: 990-024-002
Seal kit - Cartridge	Viton: 990-024-006
Seal kit - Cartridge	Buna: 990-024-007
Seal kit - Cartridge	EPDM: 990-024-014
Seal kit - Cartridge	Polyurethane: 990-024-002
Seal kit - Cartridge	Viton: 990-024-006

OPTION SELECTION EXAMPLE: FVFA8AN

(A)

(N)

A	.2 - 50 gpm (1 - 200 L/min.)
B	.2 - 50 gpm (1 - 200 L/min.)

N	E EPDM	V
----------	--------	---

TECHNICAL FEATURES

- +/- 10%
- T-8A 3 2
- 3 3000 psi (210 bar)
- -8 T-8A
-
-
- 4 1 150 psi (10,5 bar) 2
- 2 3
-
- -8 T-8A
- Sun /
- EPDM EPDM

PERFORMANCE CURVES

