



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

|                            |                           |
|----------------------------|---------------------------|
| cavidad                    | T-8A                      |
| Series                     | P                         |
| Capacity                   | 2 L/min.                  |
| Maximum Operating Pressure | 350 bar                   |
| Valve Hex Size             | 22,2 mm                   |
| Valve Installation Torque  | 27 - 33 Nm                |
| Seal kit - Cartridge       | Buna: 990-008-007         |
| Seal kit - Cartridge       | EPDM: 990-008-014         |
| Seal kit - Cartridge       | Polyurethane: 990-008-002 |
| Seal kit - Cartridge       | Viton: 990-008-006        |
| Seal kit - Cartridge       | Buna: 990-008-007         |
| Seal kit - Cartridge       | EPDM: 990-008-014         |
| Seal kit - Cartridge       | Polyurethane: 990-008-002 |
| Seal kit - Cartridge       | Viton: 990-008-006        |

## OPTION SELECTION EXAMPLE: FXAAXAN

| CONTROL                 | (X) | FLOW RATE                                       | (A) | SEAL MATERIAL   | (N) | MATERIAL/COATING                       |
|-------------------------|-----|---|-----|-----------------|-----|--|
| <b>X</b> Not Adjustable |     | <b>A</b> 15 in <sup>3</sup> /min. (250 cc/min.) |     | <b>N</b> Buna-N |     | Standard Material/Coating              |
|                         |     | <b>B</b> 20 in <sup>3</sup> /min. (330 cc/min.) |     | <b>E</b> EPDM   |     | <b>/AP</b> Stainless Steel, Passivated |
|                         |     | <b>D</b> 40 in <sup>3</sup> /min. (660 cc/min.) |     | <b>V</b> Viton  |     | <b>/LH</b> Mild Steel, Zinc-Nickel     |
|                         |     | <b>F</b> 60 in <sup>3</sup> /min. (1 L/min.)    |     |                 |     |  |
|                         |     | <b>H</b> 80 in <sup>3</sup> /min. (1.3 L/min.)  |     |                 |     |  |
|                         |     | <b>J</b> 100 in <sup>3</sup> /min. (1.6 L/min.) |     |                 |     |  |
|                         |     | <b>L</b> 120 in <sup>3</sup> /min. (2.0 L/min.) |     |                 |     |  |

### PERFORMANCE CURVES

