



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

| | |
|----------------------------|---------------------------|
| cavidad | T-8A |
| Series | P |
| Capacity | 2 L/min. |
| Maximum Operating Pressure | 350 bar |
| Valve Hex Size | 22,2 mm |
| Valve Installation Torque | 27 - 33 Nm |
| Seal kit - Cartridge | Buna: 990-008-007 |
| Seal kit - Cartridge | EPDM: 990-008-014 |
| Seal kit - Cartridge | Polyurethane: 990-008-002 |
| Seal kit - Cartridge | Viton: 990-008-006 |

OPTION SELECTION EXAMPLE: FXAAXAN

| CONTROL | (X) | FLOW RATE | (A) | SEAL MATERIAL | (N) | MATERIAL/COATING |
|-------------------------|-----|---|-----|-----------------|-----|--|
| X Not Adjustable | | A 15 in ³ /min. (250 cc/min.) | | N Buna-N | | Standard Material/Coating |
| | | B 20 in ³ /min. (330 cc/min.) | | E EPDM | | /AP Stainless Steel, Passivated |
| | | D 40 in ³ /min. (660 cc/min.) | | V Viton | | /LH Mild Steel, Zinc-Nickel |
| | | F 60 in ³ /min. (1 L/min.) | | | | |
| | | H 80 in ³ /min. (1.3 L/min.) | | | | |
| | | J 100 in ³ /min. (1.6 L/min.) | | | | |
| | | L 120 in ³ /min. (2.0 L/min.) | | | | |

PERFORMANCE CURVES

