



Fixed-orifice, pressure-compensated flow controls provide precise flow regulation for meter-in or meter-out applications where there may be wide pressure fluctuations. A variety of flow rates are available.

**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	5000 psi
Seal kit - Cartridge	Buna: 990-008-007
Seal kit - Cartridge	EPDM: 990-008-014
Seal kit - Cartridge	Polyurethane: 990-008-002
Seal kit - Cartridge	Viton: 990-008-006

**CONFIGURATION OPTIONS**

**Model Code Example: FXAAXANV**

CONTROL	(X)	FLOW RATE	(A)	SEAL MATERIAL	(V)	MATERIAL/COATING
<b>X</b> Not Adjustable		<b>A</b> 15 in <sup>3</sup> /min. (250 cc/min.)		<b>V</b> Viton		Standard Material/Coating
		<b>B</b> 20 in <sup>3</sup> /min. (330 cc/min.)		<b>E</b> EPDM		<b>JAP</b> Stainless Steel, Passivated
		<b>D</b> 40 in <sup>3</sup> /min. (660 cc/min.)		<b>N</b> Buna-N		<b>LH</b> Mild Steel, Zinc-Nickel
		<b>F</b> 60 in <sup>3</sup> /min. (1 L/min.)				
		<b>H</b> 80 in <sup>3</sup> /min. (1.3 L/min.)				
		<b>J</b> 100 in <sup>3</sup> /min. (1.6 L/min.)				
		<b>L</b> 120 in <sup>3</sup> /min. (2.0 L/min.)				