



**CONFIGURATION**

L	Control	Tuning Adjustment
A	Setting Range	orificio fijo .1 - 3 gpm (0,4 - 11 L/min.)
N	Seal Material	Buna-N
	Material/Coating	

**TECHNICAL DATA**

Maximum Operating Pressure	350 bar
Locknut Hex Size	15 mm
Locknut Torque	9 - 10 Nm
Seal kit - Cartridge	Buna: 990-162-007
Seal kit - Cartridge	EPDM: 990-162-014
Seal kit - Cartridge	Polyurethane: 990-162-002
Seal kit - Cartridge	Viton: 990-162-006
Seal kit - Cartridge	Buna: 990-162-007
Seal kit - Cartridge	EPDM: 990-162-014
Seal kit - Cartridge	Polyurethane: 990-162-002
Seal kit - Cartridge	Viton: 990-162-006

**CONFIGURATION OPTIONS**

**Model Code Example: FXBALAN**

CONTROL	(L)	SETTING RANGE	(A)	SEAL MATERIAL	(N)	MATERIAL/COATING	(/LH)
L	Tuning Adjustment	A	orificio fijo .1 - 3 gpm (0,4 - 11 L/min.)	N	Buna-N	/LH	Mild Steel, Zinc-Nickel
X	Not Adjustable			E	EPDM	/AP	Stainless Steel, Passivated
				V	Viton		Standard Material/Coating