



**CONFIGURATION**

<b>L</b>	Control	Tuning Adjustment
<b>A</b>	Setting Range	orificio fijo .1 - 3 gpm (0,4 - 11 L/min.)
<b>N</b>	Seal Material	Buna-N
	Material/Coating	

NOTE: DATA MAY VARY BY MANUFACTURING TOLERANCES. SEE CONFIGURATION SECTION.

**TECHNICAL DATA**

cavidad	T-162A
Series	0
Capacity	11 L/min.
Maximum Operating Pressure	350 bar
Valve Hex Size	19,1 mm
Valve Installation Torque	27 - 33 Nm
Adjustment Screw Internal Hex Size	4 mm
Locknut Hex Size	15 mm
Locknut Torque	9 - 10 Nm
Model Weight	0.10 kg.
Seal kit - Cartridge	Buna: 990-162-007
Seal kit - Cartridge	EPDM: 990-162-014
Seal kit - Cartridge	Polyurethane: 990-162-002
Seal kit - Cartridge	Viton: 990-162-006
Seal kit - Cartridge	Buna: 990-162-007
Seal kit - Cartridge	EPDM: 990-162-014
Seal kit - Cartridge	Polyurethane: 990-162-002
Seal kit - Cartridge	Viton: 990-162-006

## OPTION SELECTION EXAMPLE: FXBALAN

CONTROL	(L)	SETTING RANGE	(A)	SEAL MATERIAL	(N)	MATERIAL/COATING	(/LH)	
L		Tuning Adjustment	A		N	Buna-N	/LH	Mild Steel, Zinc-Nickel
C		Tamper Resistant - Factory Set		E		EPDM	/AP	Stainless Steel, Passivated
K		manilla		V		Viton		Standard Material/Coating
X		Not Adjustable						

### PERFORMANCE CURVES

