



Fixed-orifice, pressure-compensated flow controls provide precise flow regulation for meter-in or meter-out applications where there may be wide pressure fluctuations. The flow setting is specified by the user and is set at the factory.

**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	5000 psi
Locknut Hex Size	9/16 in.
Locknut Torque	80 - 90 lbf in.
Seal kit - Cartridge	Buna: 990-162-007
Seal kit - Cartridge	EPDM: 990-162-014
Seal kit - Cartridge	Polyurethane: 990-162-002
Seal kit - Cartridge	Viton: 990-162-006

**CONFIGURATION OPTIONS**

**Model Code Example: FXBAXAN**

CONTROL	(X)	SETTING RANGE	(A)	SEAL MATERIAL	(N)	MATERIAL/COATING
<b>X</b> Not Adjustable		<b>A</b> Fixed Orifice .1 - 3 gpm (0,4 - 11 L/min.)		<b>N</b> Buna-N		Standard Material/Coating
<b>C</b> Tamper Resistant - Factory Set				<b>E</b> EPDM		<b>/AP</b> Stainless Steel, Passivated
<b>K</b> Handknob				<b>V</b> Viton		<b>/LH</b> Mild Steel, Zinc-Nickel
<b>L</b> Tuning Adjustment						