



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-162A
Series	0
Capacity	11 L/min.
Maximum Operating Pressure	350 bar
Valve Hex Size	19,1 mm
Valve Installation Torque	27 - 33 Nm
Adjustment Screw Internal Hex Size	4 mm
Locknut Hex Size	15 mm
Locknut Torque	9 - 10 Nm
Model Weight	0.07 kg.
Seal kit - Cartridge	Buna: 990-162-007
Seal kit - Cartridge	Polyurethane: 990-162-002
Seal kit - Cartridge	Viton: 990-162-006
Seal kit - Cartridge	Buna: 990-162-007
Seal kit - Cartridge	Polyurethane: 990-162-002
Seal kit - Cartridge	Viton: 990-162-006

## OPTION SELECTION EXAMPLE: FXBCXCN

CONTROL	(X)	FLOW RATE	(C)	SEAL MATERIAL	(N)
<b>X</b> Not Adjustable		<b>C</b> .106 gpm (.4 L/min.)		<b>N</b> Buna-N	
<b>C</b> Tamper Resistant - Factory Set		<b>D</b> .132 gpm (.49 L/min.)		<b>V</b> Viton	
<b>K</b> manilla		<b>F</b> .198 gpm (.75 L/min.)			
<b>L</b> Tuning Adjustment		<b>G</b> .291 gpm (1.10 L/min.)			
		<b>H</b> .41 gpm (1.55 L/min.)			
		<b>J</b> .528 gpm (2.0 L/min.)			
		<b>K</b> .661 gpm (2.50 L/min.)			
		<b>L</b> .819 gpm (3.10 L/min.)			
		<b>M</b> 1.057 gpm (4.00 L/min.)			
		<b>N</b> 1.321 gpm (5.00 L/min.)			
		<b>P</b> 1.585 gpm (6.0 L/min.)			
		<b>R</b> 2.008 gpm (7.6 L/min.)			
		<b>S</b> 2.378 gpm (9.0 L/min.)			
		<b>T</b> 2.642 gpm (10.0 L/min.)			
		<b>V</b> 3.012 gpm (11.40 L/min.)			

### PERFORMANCE CURVES

