



### CONFIGURATION

<b>L</b> Control	Tuning Adjustment
<b>A</b> Setting Range	Replaceable Orifice .1 - 12 gpm (0,4 - 45 L/min.)
<b>N</b> Seal Material	Buna-N
	Material/Coating

Fixed-orifice, pressure-compensated flow controls provide precise flow regulation for meter-in or meter-out applications where there may be wide pressure fluctuations. The flow setting is specified by the user and is set at the factory.

### TECHNICAL DATA

Maximum Operating Pressure	5000 psi
Locknut Hex Size	9/16 in.
Locknut Torque	80 - 90 lbf in.
Seal kit - Cartridge	Buna: 990-203-007
Seal kit - Cartridge	EPDM: 990-203-014
Seal kit - Cartridge	Viton: 990-203-006

### CONFIGURATION OPTIONS

#### Model Code Example: FXDALAN

CONTROL	(L)	SETTING RANGE	(A)	SEAL MATERIAL	(N)	MATERIAL/COATING	(/LH)
<b>L</b> Tuning Adjustment		<b>A</b> Replaceable Orifice .1 - 12 gpm (0,4 - 45 L/min.)		<b>N</b> Buna-N		<b>/LH</b> Mild Steel, Zinc-Nickel	
<b>C</b> Tamper Resistant - Factory Set				<b>E</b> EPDM		<b>/AP</b> Stainless Steel, Passivated	
<b>K</b> Handknob				<b>V</b> Viton		Standard Material/Coating	
<b>X</b> Not Adjustable							