



CONFIGURATION

L Control	Tuning Adjustment
A Setting Range	Replaceable Orifice .1 - 12 gpm (0,4 - 45 L/min.)
N Seal Material	Buna-N
	Material/Coating

TECHNICAL DATA

Maximum Operating Pressure	350 bar
Locknut Hex Size	15 mm
Locknut Torque	9 - 10 Nm
Seal kit - Cartridge	Buna: 990-203-007
Seal kit - Cartridge	EPDM: 990-203-014
Seal kit - Cartridge	Viton: 990-203-006
Seal kit - Cartridge	Buna: 990-203-007
Seal kit - Cartridge	EPDM: 990-203-014
Seal kit - Cartridge	Viton: 990-203-006

CONFIGURATION OPTIONS

Model Code Example: FXDALAN

CONTROL	(L)	SETTING RANGE	(A)	SEAL MATERIAL	(N)	MATERIAL/COATING	(/LH)
L Tuning Adjustment		A Replaceable Orifice .1 - 12 gpm (0,4 - 45 L/min.)		N Buna-N		/LH Mild Steel, Zinc-Nickel	
C Tamper Resistant - Factory Set		B Permanent Orifice .1 - 12 gpm (0,4 - 45 L/min.)		E EPDM		/AP Stainless Steel, Passivated	
K manilla				V Viton		Standard Material/Coating	
X Not Adjustable							