



CONFIGURATION

L Control	Tuning Adjustment
A Setting Range	Replaceable Orifice .1 - 12 gpm (0,4 - 45 L/min.)
N Seal Material	Buna-N
Material/Coating	

NOTE: DATA MAY VARY FROM TECHNICAL DATA SEE CONFIGURATION SECTION.

cavidad	T-5A
Series	2
Capacity	45 L/min.
Maximum Operating Pressure	350 bar
Valve Hex Size	28,6 mm
Valve Installation Torque	61 - 68 Nm
Adjustment Screw Internal Hex Size	4 mm
Locknut Hex Size	15 mm
Locknut Torque	9 - 10 Nm
Model Weight	0.26 kg.
Seal kit - Cartridge	Buna: 990-203-007
Seal kit - Cartridge	EPDM: 990-203-014
Seal kit - Cartridge	Viton: 990-203-006
Seal kit - Cartridge	Buna: 990-203-007
Seal kit - Cartridge	EPDM: 990-203-014
Seal kit - Cartridge	Viton: 990-203-006

OPTION SELECTION EXAMPLE: FXDALAN

CONTROL	(L) SETTING RANGE	(A) SEAL MATERIAL	(N) MATERIAL/COATING
L Tuning Adjustment	A Replaceable Orifice .1 - 12 gpm (0,4 - 45 L/min.)	N Buna-N	/LH Mild Steel, Zinc-Nickel
C Tamper Resistant - Factory Set	B Permanent Orifice .1 - 12 gpm (0,4 - 45 L/min.)	E EPDM	/AP Stainless Steel, Passivated
K manilla		V Viton	Standard Material/Coating
X Not Adjustable			

PERFORMANCE CURVES

