



CARACTÉRISTIQUES NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Pression maximale de fonctionnement	350 bar
Couple de serrage du contre écrou	9 - 10 Nm
Dimension du contre-écrou sur plat	15 mm
Seal kit - Cartridge	Buna: 990-203-007
Seal kit - Cartridge	EPDM: 990-203-014
Seal kit - Cartridge	Viton: 990-203-006
Seal kit - Cartridge	Buna: 990-203-007
Seal kit - Cartridge	EPDM: 990-203-014
Seal kit - Cartridge	Viton: 990-203-006

CONFIGURATION OPTIONS

Model Code Example: FXDCLXAN

DISPOSITIF DE CONTRÔLE	(L)	VALEUR DE DÉBIT	(A)	MATIÈRE DES JOINTS	(N)
L Vis de Réglage Standard		A .106 gpm (.4 L/min.)		N Buna N	
X Non Réglable		B .264 gpm (1.0 L/min.)		V Viton	
		C .528 gpm (2.0 L/min.)			
		D .793 gpm (3.0 L/min.)			
		F .991 gpm (3.75 L/min.)			
		G 1.215 gpm (4.6 L/min.)			
		H 1.479 gpm (5.6 L/min.)			
		J 1.823 gpm (6.9 L/min.)			
		K 2.245 gpm (8.5 L/min.)			
		L 2.774 gpm (10.5 L/min.)			
		M 3.434 gpm (13.0 L/min.)			
		N 4.227 gpm (16.0 L/min.)			
		P 5.178 gpm (19.6 L/min.)			
		R 6.472 gpm (24.5 L/min.)			
		S 7.925 gpm (30.0 L/min.)			
		T 9.774 gpm (37.0 L/min.)			
		V 11.888 gpm (45.0 L/min.)			