



Fixed-orifice, pressure-compensated flow controls provide precise flow regulation for meter-in or meter-out applications where there may be wide pressure fluctuations. The flow setting is specified by the user and is set at the factory.

TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	5000 psi
Locknut Hex Size	9/16 in.
Locknut Torque	80 - 90 lbf in.
Seal kit - Cartridge	Buna: 990-016-007
Seal kit - Cartridge	EPDM: 990-016-014
Seal kit - Cartridge	Polyurethane: 990-016-002
Seal kit - Cartridge	Viton: 990-016-006

CONFIGURATION OPTIONS

Model Code Example: FXEAXAN

CONTROL	(X)	SETTING RANGE	(A)	SEAL MATERIAL	(N)	MATERIAL/COATING
X Not Adjustable		A Replaceable Orifice .2 - 25 gpm (0,8 - 95 L/min.)		N Buna-N		Standard Material/Coating
C Tamper Resistant - Factory Set		B Permanent Orifice .2 - 25 gpm (0,8 - 95 L/min.)		E EPDM		/AP Stainless Steel, Passivated
K Handknob				V Viton		/LH Mild Steel, Zinc-Nickel
L Tuning Adjustment						