



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-16A
	3
	95 L/min.
	350 bar
	31,8 mm
	203 - 217 Nm
	4 mm
	15 mm
	9 - 10 Nm
	0.47 kg.
Seal kit - Cartridge	Buna: 990-016-007
Seal kit - Cartridge	EPDM: 990-016-014
Seal kit - Cartridge	Polyurethane: 990-016-002
Seal kit - Cartridge	Viton: 990-016-006
Seal kit - Cartridge	Buna: 990-016-007
Seal kit - Cartridge	EPDM: 990-016-014
Seal kit - Cartridge	Polyurethane: 990-016-002
Seal kit - Cartridge	Viton: 990-016-006

OPTION SELECTION EXAMPLE: FXEAXAN

	(X)	(A)	(N)	MATERIAL/COATING
X	A	.2 - 25 gpm (0,8 - 95 L/min.)	N	Standard Material/Coating
L	B	.2 - 25 gpm (0,8 - 95 L/min.)	E EPDM	/AP
			V	/LH -

TECHNICAL FEATURES

- ±10%
- EPDM
- 2
- ±25%
- "/AP"
- Sun

PERFORMANCE CURVES

