



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-11A
Series	1
Capacity	40 L/min.
Maximum Operating Pressure	350 bar
Check Cracking Pressure	2 bar
Manual Override Force Requirement	33 N/100 bar @ Port 1
Manual Override Stroke	2,5 mm
Maximum Valve Leakage at 110 SUS (24 cSt)	0,7 cc/min.@350 bar
Response Time - Typical	50 ms
Switching Frequency	15,000 max. cycles/hr
Solenoid Tube Diameter	19 mm
Valve Hex Size	22,2 mm
Valve Installation Torque	41 - 47 Nm
Seal and nut kit - Coil	Viton: 990-770-006
Seal kit - Cartridge	Buna: 990-011-007
Seal kit - Cartridge	Polyurethane: 990-011-002
Seal kit - Cartridge	Viton: 990-011-006

OPTION SELECTION EXAMPLE: HDDAXCN

CONTROL	(X) SPOOL CONFIGURATION	(C) SEAL MATERIAL	(N) BOBINA
X No Manual Override	C normalmente cerrado	N Buna-N	No coil
D Twist/Lock (Dual) Manual Override		V Viton	212 DIN 43650-Form A, 12 VDC
L Twist/Lock (Detent) Manual Override			224 DIN 43650-Form A, 24 VDC
M activador manual			912 Deutsch DT04-2P, 12 VDC
T Twist (Momentary) Manual Override			924 Deutsch DT04-2P, 24 VDC

PERFORMANCE CURVES

